




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B23K 26/04	A1	(11) International Publication Number: WO 98/50196 (43) International Publication Date: 12 November 1998 (12.11.98)
<p>(21) International Application Number: PCT/SE98/00838</p> <p>(22) International Filing Date: 6 May 1998 (06.05.98)</p> <p>(30) Priority Data: 9701710-7 7 May 1997 (07.05.97) SE</p> <p>(71) Applicant (for all designated States except US): INSTITUTET FÖR VERKSTADSTEKNISK FORSKNING [SE/SE]; Argongatan 30, S-431 53 Mölndal (SE).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): NILSSON, Thomas [SE/SE]; Fullblodsgatan 4B, S-431 32 Mölndal (SE). VON BRÖMSEN, Bernt [SE/SE]; Träkilsgatan 17, S-416 78 Göteborg (SE).</p> <p>(74) Agent: GÖTEBORGS PATENTBYRÅ; Sjöporten 4, S-417 64 Göteborg (SE).</p>	<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p>	

(54) Title: DEVICE FOR DETECTING AND CALCULATING THE FOCUS POINT POSITION, SHAPE AND POWER DISTRIBUTION OF A LASER BEAM

(57) Abstract

Device for detecting and calculating focus point position (2), shape (3) and power distribution of a laser beam after a focussing lens, and which at least incorporates a laser source (10), the focussing lens (4), a light affecting body (5, 6), a light sensor (7), and means for calculation (9). The device is characterized in that the focussing lens (4), the light affecting body (5, 6) and the light sensor (7) are arranged so that their relative distance is changeable, that the laser beam (1) and the light affecting body (5, 6) are arranged to perform a relative movement consisting of one or more tracing movements through the beam path, preferably in at least one plane and with different relative distances, that the light sensor (7) is arranged to measure at least a fraction of the laser light (1) emitted by the light affecting body (5, 6), and that the light sensor (7) is arranged to produce an output signal (8) which is arranged to be received by a calculating means (9) for calculation of focus point position (2), shape (3) and power distribution.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

DEVICE FOR DETECTING AND CALCULATING THE FOCUS POINT POSITION,
SHAPE AND POWER DISTRIBUTION OF A LASER BEAM

TECHNICAL FIELD

5 The invention relates to a device for detecting and calculating focus point position, shape and power distribution of a laser beam after a focussing lens, and which at least incorporates a laser source, the focussing lens, a light affecting body, a light sensor, and means for calculation.

10

BACKGROUND OF THE INVENTION

As automation increases in industry and increased complexity when choosing materials lasers become increasingly important. Especially promising is the Nd:YAG laser, which is very well
15 suited to be integrated with a robot, but also carbon dioxide and excimer lasers are important for industry. There are also other lasers, which industrial applicability is high.

In this kind of inventions, there is often a lens having the
20 purpose of focussing the laser beam in desired way. A consequence of the presence of the lens is that the laser beam appears with a waist, i.e. a shape which in the direction of the beam first presents a narrowing feature, which thereafter becomes wider. The processing effect of the laser beam is
25 naturally at maximum where the beam presents its smallest surface. Therefore, it is interesting to be able to position the laser simply and effectively in order to accomplish this.

Today, one way of measuring the position of the focus point
30 position, which should be the same as the tool center point of the robot, is based on the assistance of a visual assisting

laser and manually moving the robot in order to position the focus point position in a well-defined position in space. This is normally time-consuming and gives an obvious lack of precision.

5

In SE-447 972 a method for detecting a focus point position for a device processing with a laser is presented. It is characterized by a light shielding element, which can shield a fraction of the laser beams and a light sensor, produces an output signal. The output signal is proportional to the amount of laser light having passed through the light shielding element. The searching for focus is arranged so that at least the light shielding element or the light sensor is moved in direction of the optical axis for detection of the position, at which the output signal of the light sensor is at its maximum or at its minimum. Based on the minimum or maximum output signal of the light sensor the focus point position is detected. It should be noted that the invention described in this document only detects the focus point position and does not deal with the shape or power distribution of the laser beam.

10

15

20

PURPOSE OF THE INVENTION AND ITS MOST CHARACTERISING FEATURES

25

30

An area within which the present invention can be used is processing of various materials (e.g. metals and plastics) such as welding, cutting, soldering and hardening with a laser. In these cases a high power laser is used. It should be noted that the invention preferably also can be used in connection with low power lasers, for instance when positioning of robots intended for automatized spray painting. In this case a previously known low power laser and a focussing lens are

arranged to the robot, or robots at machines with multiple axes, so that the focus point position of the laser always coincides with the tool center point, also known as TCP, if this has been chosen in a free point in the vicinity of the machine. Thus, the present invention can here be used to determine the tool center point of a robot or another machine, even if the tool is of another kind than a laser.

The present invention is constituted by that a focussing lens, the light affecting body and the light sensor are arranged so that their relative distances are adjustable, that the laser beam and the light affecting body are arranged to perform a relative movement consisting of one or more tracing movements through the beam path, preferably in at least one plane and with different relative distances, that the light sensor is arranged to measure at least a fraction of the laser light emitted by the light affecting body, and that the light sensor is arranged to produce an output signal which is arranged to be received by a calculating means for calculation of focus point position, shape and power distribution.

DESCRIPTION OF THE DRAWINGS

The invention will be described below with reference to the appended drawings showing the preferred embodiment.

Figure 1 shows an embodiment of how the present invention can be implemented.

Figure 2 shows schematically an embodiment of a transmitting light affecting body, which in this case is constituted by an

optical fiber, which is illuminated by a laser beam.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Figure 1 shows an embodiment of the present invention. This example is intended to be used in connection to the working area, i.e. where, e.g. the cutting with a high power laser can take place. It is possible to put the embodiment besides a working area or at different places in the working area, in order to detect and calculate the focus point position 2, shape 3 and power distribution of the laser beam 1 when necessary after a focussing lens 4, at different locations in the working area. Uniform quality can then be obtained in the whole working area. In figure 2, an optical fiber 5, a sensor 7 and a laser beam 1 are presented. The laser beam 1 is arranged onto the optical fiber 5. In figure 1, two optical fibers 5, 6 are presented, which fibers are parallel, but this is not an absolute condition in order to achieve the purpose of the invention. However, there is a distance between them, if you relate to the direction of the laser beam 1. Important in this embodiment is that the laser beam 1 is transmitted through them. When the laser beam 1 is transmitted, also a certain diversion of the beam along the longitudinal axis of the optical fiber takes place. A fraction of this diversified radiation exits the optical fiber radially to be detected by a sensor 7, which can be previously known. Another possibility is to arrange a number of light sensors with different light sensitivity which together generate a measure of the power of the beam with scales. The output signal of the sensor 8 is connected to a means for calculation 9, which object is to calculate the focus point position 2, shape 3 and power distribution of the laser beam 1. It should be noted that the

laser beam is generated by a laser source 10 which is suitable for the task. One of the calculations is based on basic formulae describing the shape of a laser beam, $d(z)$, after it has passed through a focussing lens 4;

5

$d(z) = d_0 \sqrt{1 + (z/z_0)^2}$, where

10

d_0 is the width of the beam in the focus point position, z_0 is a constant describing the optical device and z is the distance from the focus point position in direction of the beam. In a simple case when a beam traces perpendicularly to a fiber, the formula above is sufficient. Then you have to do at least two traces with the laser beam. In other cases the problem can be solved by introducing an angle parameter in the equation, which then appears more complicated. In the latter case when the beam is inclined and thus deviates from the traditional z -direction, an extra trace is necessary in order to find the focus point position. Generally, it can be said that an increased number of fibers, or more generally light affecting bodies, lead to the need of a lower number of traces of the laser beam over the fibers/bodies.

15

20

25

30

In the preferred embodiment in figure 1, there are two optical fibers 5, 6 and two sensors 7, which in this case are identical. They do not necessarily have to be identical. Both sensors 7 are connected to the means for calculation 9, which based on the output signals 8 of the sensor 7, calculates the focus point position 2, shape 3 and power distribution of the laser beam 1. The laser beam 1 is arranged to trace over the optical fibers 5, 6 at a certain distance. The shape 2 of the

beam 1 is calculated from the radiation, which one or more light sensors 7 detect at the traces. If the power of laser beam 1 is homogenous in its cross section a Gauss-like distribution can be detected. If further traces are necessary the distance between the fibers 5, 6 and the focussing lens 4 are changed and the laser beam 1 traces over the fibers 5, 6 once again. Based on the information which can be detected from the traces, the focus point position 2, shape 3 and power distribution of the laser beam 1 can be determined.

When the focus point position 2, shape 3 and power distribution of the laser beam 1 has been determined by the means for calculation 9, this information is used to control the processing tool, which e.g. can be equipment for welding, cutting, soldering and hardening or a spraying nozzle. Also, the device can be applied in other processes, where it is important to know the tool center point. It is also conceivable that the produced information is used as information to the user.

It should be noted that previously known filters may be necessary in order to filter the output signals 8 from the sensors 7 in order to increase the precision in the result from the invention. These may be placed e.g. in the vicinity of the means for calculation 9.

Also, it should be noted that the light affecting body, which is mentioned in the appended patent claims, does not have to be one or several optical fibers, but also other transmitting suitable bodies are sufficient to achieve the purpose of the invention.

An alternative to a transmitting body is a reflecting body, which also can be used in the invention to achieve the purpose. In such a case, the sensor is placed in such a manner that it absorbs directly reflected radiation from the body. An example
5 of such a body is one which to a large extent consists of silver. Such a body can be of arbitrary, known geometry. For instance a limited area of the surface of the light affecting body 5, 6 can be processed so that the direction of the reflected radiation from the limited area clearly deviates from the
10 direction of the rest of the radiation. Thereby the intensity of the beam in a point can be determined by one or several suitably placed sensors 7.

Another alternative to a transmitting or reflecting body is an
15 absorbing body. These can only be used with low power lasers.

The power distribution of the laser beam 1 can be disturbed if the so called shielding glass, which is located after the focussing lens 4 in the direction of the laser beam 1, is
20 dirty. Then it is possible that one or several sensors detect the change based on calibration data and provide a signal to a user that the shielding glass should be checked.

Also, it could be important to note that the device according
25 to the invention must before the first time of use be calibrated from e.g. chosen type of light affecting body, location of one or more sensors, laser type and focussing lens.

It should be noted that the term light affecting body also
30 comprises fluids enclosed in a suitable casing.

CLAIMS

1. Device for detecting and calculating focus point position (2), shape (3) and power distribution of a laser beam after a focussing lens, and which at least incorporates a laser source (10), the focussing lens (4), a light affecting body (5, 6), a light sensor (7), and means for calculation (9),

characterized in,

that the focussing lens (4), the light affecting body (5, 6) and the light sensor (7) are arranged so that their relative distance is changeable,

that the laser beam (1) and the light affecting body (5, 6) are arranged to perform a relative movement consisting of one or more tracing movements through the beam path, preferably in at least one plane and with different relative distances,

that the light sensor (7) is arranged to measure at least a fraction of the laser light (1) emitted by the light affecting body (5, 6), and

that the light sensor (7) is arranged to produce an output signal (8) which is arranged to be received by a calculating means (9) for calculation of focus point position (2), shape (3) and power distribution.

2. Device according to claim 1,

characterized in,

that the light affecting body (5, 6) consists of a transmitting and/or a reflecting body.

3. Device according to claim 2,

characterized in,

that the light affecting body (5, 6) is an optical fiber.

4. Device according to claim 1,
c h a r a c t e r i z e d i n,
that the light affecting body (5, 6) consists of an absorbing
5 body when the laser source (19) is a laser of low power.

5. Device according to claim 2,
c h a r a c t e r i z e d i n,
that the light affecting body (5, 6) to a considerable extent
10 is constituted by silver.

FIG.1





FIG.2



INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 98/00838

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: B23K 26/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: B23K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4472055 A (AKIRA TSUTSUMI), 18 Sept 1984 (18.09.84), column 2, line 22 - column 7, line 18, figure 1, abstract --	1-5
A	GB 2300534 A (BLZ BAERISCHES LASERZENTRUM GEMEINNUTZIGE FORSCHUNGSGESELLSCHAFT MBH), 6 November 1996 (06.11.96), page 5, line 9 - line 20, figure 1, abstract --	1-5
A	EP 0437226 A2 (MITSUBISHI JUKOGYO KABUSHIKI KAISHA), 17 July 1991 (17.07.91), column 3, line 47 - column 4, line 47, figures 1,2, abstract --	1-5

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

21 August 1998

Date of mailing of the international search report

25 -08- 1998

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Karin Säfssten

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 98/00838

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4772772 A (W. JÜPTNER ET AL.), 20 Sept 1988 (20.09.88), column 2, line 56 - column 3, line 50, figures 1,2,5, abstract --	1-5
A	EP 0440990 A1 (INDUSTRIAL TECHNOLOGY RESEARCH INSTITUTE), 14 August 1991 (14.08.91), column 3, line 50 - column 6, line 35, figures 1,2, abstract -- -----	1-4

INTERNATIONAL SEARCH REPORT
Information on patent family members

27/07/98

International application No.
PCT/SE 98/00838

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4472055 A	18/09/84	AU 552364 B AU 7480781 A CA 1173662 A CH 656568 A,B DE 3134555 A FR 2489195 A,B GB 2083216 A,B JP 1438140 C JP 57046215 A JP 62046279 B SE 447972 B,C SE 8105214 A	29/05/86 11/03/82 04/09/84 15/07/86 08/07/82 05/03/82 17/03/82 19/05/88 16/03/82 01/10/87 12/01/87 03/03/82
GB 2300534 A	06/11/96	CA 2175730 A DE 19516376 A FR 2733707 A,B GB 9609287 D IT T0960359 A	05/11/96 14/11/96 08/11/96 00/00/00 03/11/97
EP 0437226 A2	17/07/91	SE 0437226 T3 DE 69101789 D,T JP 3207587 A US 5155329 A	15/09/94 10/09/91 13/10/92
US 4772772 A	20/09/88	DE 3623409 A DE 3777702 A EP 0252268 A,B SE 0252268 T3 JP 63030191 A	21/01/88 30/04/92 13/01/88 08/02/88
EP 0440990 A1	14/08/91	DE 69007075 D,T US 5048953 A	13/10/94 17/09/91

THIS PAGE BLANK (USPTO)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)